



## "Air Champ"<sup>®</sup>—the Ideal Motor Brake

Any of the four rugged "Air Champ" Brake models, matched with a sheave adaptor, becomes an easy-to-mount motor brake for any single shaft motor, from ½ to 25 h.p.

## Versatile—Dependable—"Air Champ"<sup>®</sup> Brakes

These units can also be used on double shafted "C" Flange motors by using adaptor plate for the motor frame sizes listed in chart.....

### DIMENSIONS—MOTOR BRAKE SHEAVE ADAPTOR

PRODUCT NUMBER	MOTOR-BRAKE ADAPTOR MODEL NO.	A BORE	B O.O.	C O.O.	D DEPTH	E LENGTH	F OVERALL LENGTH	FOR USE WITH BRAKE MODEL NO.
819500	FWB-1	0.875	1.125	1.375	2-1/4	3	5-3/4	FWB (0-1-1/2 HP)
819700	FWB-2	0.750						
819800	FWB-3	0.625						
821300	LWB-1	1.125	1.375	1.625	2-11/16	3-3/8	6-7/8	LWB (0-5 HP)
821600	LWB-2	1.000						
821700	LWB-3	0.875						
823300	MWB-1	1.625	1.9375	2.500	4	4-3/4	9	MWB (5-10 HP)
823600	MWB-2	1.375						
823700	MWB-3	1.250						
825400	HWB-1	2.125	2.9375	3.000	6-3/8	7-3/8	12-1/8	HWB (10-25 H.P.)
825700	HWB-2	1.875						

